1964 TEMPEST ENGINE IDENTIFICATION CHART

HORSEPOWER	ENGINE CODE*	DISP. CU. IN.	TYPE TRANS.	USAGE	MODEL APPL.				COMP. RATIO				CARB.				VALVE SPG.			CAM-SHFT.			DIST. MODEL			H.D. Clutch	Spec. Lifter Assy.	Spec. Closed PCV Valve (Used in Calif. Only)
					20-21-22	Taxi	Police	G.T.O.	7.2	8.6	10.5	10.75	1 BBL	2 BBL	4 BBL	3-2 BBL	Single	Std. Two	H.D. Two	3788984	524009	537441	1110316	1111054	1111052			
348	76	389	SM	Opt.				x				x				x			x		x			x			x	
325	78	389		Std.				x				x			x				x		x			x			x	
140	80	215		Std.	x					x			x				x			x			x					
140	81	215		Opt.	x					x			x				x			x			x					x
125	82	215		Export	x				x				x				x			x			x					
140	84	215		Std.		x	x			x			x				x			x			x			x		
140	84	215		Opt.	x					x			x				x			x			x			x		
140	85	215		Opt.	x					x			x				x			x			x			x		x
250	92	326		Opt.	x					x				x				x				x			x			
280	97	326 HO		Opt.	x						x				x				x			x			x		x	
348	77	389	Auto	Opt.				x				x				x			x		x			x			x	
325	79	389		Std.				x				x			x				x		x			x			x	
125	87	215		Export	x				x				x				x			x			x					
140	88	215		Std.	x					x			x				x			x			x					
140	89	215		Opt.	x					x			x				x			x			x					x
250	96	326		Opt.	x					x				x				x				x			x			
280	94	326 HO		Opt.	x						x				x				x			x			x		x	

*First two digits of engine code identify engine type, remaining letters or numbers identify transmission.

TRANSMISSION CODES

Z	(3-Spd. S.M.)	215 Engine	W/O Console
Z4	(3-Spd. S.M.)	215 Engine	W Console
5	(3-Spd. S.M.)	326 Engine	W/O Console
5X	(3-Spd. S.M.)	326 Engine	W Console
X	(3-Spd. S.M.)	389 Engine	Floor Shift Only
ZW	(4-Spd. S.M.)	215 Engine	W — 3.08, 3.23, 3.36, 3.55 Axle Ratio
Z9	(4-Spd. S.M.)	215 Engine	W — 3.73, 3.90, 4.30 Axle Ratio
5W	(4-Spd. S.M.)	326 Engine	W — 3.08, 3.23, 3.36, 3.55 Axle Ratio
59	(4-Spd. S.M.)	326 Engine	W — 3.73, 3.90, 4.30 Axle Ratio
XW	(4-Spd. S.M.)	389 Engine	W — 3.08, 3.23, 3.36, 3.55 Axle Ratio
X9	(4-Spd. S.M.)	389 Engine	W — 3.73, 3.90, 4.30 Axle Ratio
Y	(Automatic)	215 Engine	
O	(Automatic)	326 Engine	
J	(Automatic)	389 Engine	